

High-performance. Capacity. Technology.

**HITACHI**  
Inspire the Next

## Hitachi Travelstar C4K40 1.8-inch hard disk drive

### Highlights

- ▶ **20 & 40 GB 4200 rpm in 9.5mm and 7.0mm high package for maximum capacity slimline portable applications**
- ▶ **300G/2ms operating shock**
- ▶ **ATA-5 interface with 2 MB data buffer**
- ▶ **Ultra DMA mode 5 (100 MB/s max.) supported**
- ▶ **GMR head and ME<sup>2</sup>PRML read channel technology**
- ▶ **Shock sensor, S.M.A.R.T.**
- ▶ **Use of Fluid Dynamic Bearing Motor to improve acoustic and shock characteristics**



### Cutting-edge storage technology

Redefining state-of-the-art storage for mobile computing, Hitachi introduces the new Hitachi Travelstar C4K40, 1.8-inch, 4200 rpm hard disk drive. Available in 20 and 40 GB, the Travelstar C4K40 leverages the award-winning Travelstar technology legacy in a new form-factor, providing high capacity storage for a wide range of portable mobile equipment.

Designed with Fluid Dynamic Bearing (FDB) motor technology, Giant Magnetoresistive (GMR) heads, and a ME<sup>2</sup>PRML read channels for exceptional quietness and performance required by today's demanding computing needs.

### Ideal for PC, non-PC, and removable mobile storage applications

Delivering both high-capacity and performance, light-weight, with a small form factor, the Travelstar C4K40 is an ideal storage device for not only traditional computing needs, but also for non-traditional products such as handheld PDA's, MP3 players, printers, fax-copiers, and other removable storage devices.

### Performance and reliability

Incorporating both a shock sensor and Self-Monitoring Analysis and Report Technology (S.M.A.R.T.), the Travelstar C4K40 is well equipped to help maintain high-performance and fast seek times in applications that require a rugged, slimline form factor.

## Hitachi family of Travelstar C4K40 hard disk drives specifications

### Product name

Travelstar C4K40

Model number	HTC424020F7AT00 HTC424040F9AT00
--------------	------------------------------------

### Configuration

Interface	ATA-5
Capacity (GB)	40/20
Sector size (bytes)	512
Number of cylinders	38,957
Data heads	4/2
Disks	2/1

### Performance

Data buffer (MB) <sup>1</sup>	2
Rotational speed (rpm)	4,200
Latency (average ms)	71
Max. interface transfer rate (MB/sec)	100MB/sec Ultra DMA mode-5 16.6MB/sec PIO mode-4 Multiword DMA mode-2
Seek time (ms)	
1 track (typical)	3
Average (typical)	15
Full stroke (typical)	26
Read technology	ME <sup>2</sup> PRML, ID-less format
Internal transfer rate (MB/s)	16.8-29.9
Recording density (Max. Mbpm)	29.3
Track density (Mtpm)	3.54

### Reliability

Error rate (non-recoverable)	< 1 per 10 <sup>13</sup> bits transferred
Preventative maintenance	Not required

### Power

Requirement	+3.3VDC(±5%)	+5VDC(±5%)
Seek (average)	1.122 W	1.7 W
Spin up (average)	1.485 W	2.25 W
Active idle (average)	0.33W	0.5W
Write (average)	1.555 W	1.75W
Sleep	0.066W	0.1W
Standby (average)	0.099 W	0.15W

### Physical size

Height (mm)	9.5 (2 disk) / 7.0 (1 disk)
Width (mm)	70
Depth (mm)	60
Weight (g)	62 (2 disk) / 47 (1 disk)

### Environmental characteristics

#### Operating

Ambient temperature	5° to 55° C (5V) / 5° to 60° C (3.3V)
Relative humidity (non-condensing)	5% - 90%
Maximum wet bulb (non-condensing)	29.4° C (84.2 °F)
Shock (half sine wave)	300G/2ms
Vibration (sine wave)	1G (22-500Hz)

#### Non-operating

Ambient temp	-40° to 70° C (-40° to 158° F)
Relative humidity (non-condensing)	5% - 95%
Maximum wet bulb (non-condensing)	40° C (104° F)
Shock (half sine wave)	1,000G/1ms (2 disk) 1,200G/1ms (1 disk)
Vibration (sine wave)	5G (22-500Hz)

### Acoustics (A-Weighted Sound Power (Bels))

Idle (typical)	2.0 (2 disk) 1.8 (1 disk)
Seek (typical)	2.6 (2 disk) 2.5 (1 disk)

**HITACHI**  
Inspire the Next

Hitachi Global Storage Technologies

### For more information

#### Internet and e-mail:

- www.hgst.com
- N. America: support\_usa@hgst.com
- EMEA: support\_uk@hgst.com
- Asia Pacific: support\_sg@hgst.com

#### Hitachi hard drive product information:

- US: 1 888 426-5214
- For a complete list of worldwide phone numbers, visit www.hgst.com/support

© Copyright Hitachi Global Storage Technologies 2003

Hitachi Global Storage Technologies  
5600 Cottle Road  
San Jose, CA 95193

Produced in the United States  
7/03  
All rights reserved

<sup>1</sup> Space reserved for firmware

Travelstar™ is a trademark of  
Hitachi Global Storage Technologies.

Other product names are trademarks or registered  
trademarks of their respective companies.

Adaptive Battery Life Extender, and Drive Fitness Test  
are trademarks of Hitachi Global Storage Technologies.

References in this publication to Hitachi Global Storage  
Technologies products, programs or services do not  
imply that Hitachi Global Storage Technologies intends  
to make these available in all countries in which Hitachi  
Global Storage Technologies operates.

Product information is provided for information pur-  
poses only and does not constitute a warranty.

Information is true as of the date of publication and is  
subject to change. Actual results may vary.

This publication is for general guidance only.

Photographs may show design models.