

431-RQMT-000004

Revision -

Effective Date: To be added upon Release

Expiration Date: To be added upon Release

**DRAFT**

**Robotic Lunar Exploration Program  
Lunar Reconnaissance Orbiter Project**

**Mission Requirements Document**

**07/20/2005**



---

**Goddard Space Flight Center  
Greenbelt, Maryland**

---

**National Aeronautics and  
Space Administration**

CHECK WITH RLEP DATABASE AT:  
<https://lunarngin.gsfc.nasa.gov>  
TO VERIFY THAT THIS IS THE CORRECT VERSION PRIOR TO USE.

## CM FOREWORD

This document is a Lunar Reconnaissance Orbiter (LRO) Project Configuration Management (CM)-controlled document. Changes to this document require prior approval of the applicable Configuration Control Board (CCB) Chairperson or designee. Proposed changes shall be submitted to the LRO CM Office (CMO), along with supportive material justifying the proposed change. Changes to this document will be made by complete revision.

Questions or comments concerning this document should be addressed to:

LRO Configuration Management Office  
Mail Stop 431  
Goddard Space Flight Center  
Greenbelt, Maryland 20771

**Signature Page**

***Prepared by:***

Martin Houghton LRO Mission Systems Engineer GSFC/NASA Code 591	Date
---	------

***Reviewed by: Instruments***

I. Mitrofanov LEND ISR, Moscow	Date	D. Spence CRaTER Boston University	Date
--------------------------------------	------	--	------

D. Smith LOLA NASA/GSFC	Date	M. Robinson LROC Northwestern University	Date
-------------------------------	------	--	------

D. Page Diviner UCLA	Date	S. Stern LAMP SWRI	Date
----------------------------	------	--------------------------	------

***Reviewed by: Subsystems Leads***

Jason Soloff Communications <Enter Org/Code Here>	Date	Quang Nguyen C&DH <Enter Org/Code Here>	Date
---	------	---	------

**Signature Page*****Reviewed by: Subsystem leads***

_____ Mark Beckman Flight Dynamics <Enter Org/Code Here>	_____ Date	_____ Eric Holmes GN&C <Enter Org/Code Here>	_____ Date
_____ Mike Blau Software <Enter Org/Code Here>	_____ Date	_____ Rick Saylor Ground System <Enter Org/Code Here>	_____ Date
_____ Giulio Rosanova Mechanical <Enter Org/Code Here>	_____ Date	_____ Rick Kinder Electrical <Enter Org/Code Here>	_____ Date
_____ Chuck Zakrzwski Propulsion <Enter Org/Code Here>	_____ Date	_____ Tom Spitzer Power <Enter Org/Code Here>	_____ Date
_____ Charles Baker Thermal <Enter Org/Code Here>	_____ Date	_____ Tom Jones Launch Vehicle Manager <Enter Org/Code Here>	_____ Date

**Signature Page**

***Reviewed by: Systems***

Joanne Baker I&T Systems Engineer GSFC/NASA Code	Date	Arlin Bartels Payload Systems Manager GSFC/NASA Code 591	Date
--	------	--	------

Phil Luers Electrical Systems <Enter Org/Code Here>	Date	Mike Prybzy Spacecraft Systems <Enter Org/Code Here>	Date
---	------	--	------

***Approved by:***

<Enter Name Here> <Enter Position Title Here> <Enter Org/Code Here>	Date	<Enter Name Here> <Enter Position Title Here> <Enter Org/Code Here>	Date
---	------	---	------

***Concurred by:***

Craig Tooley LRO Project Manager <Enter Org/Code Here>	Date	<Enter Name Here> <Enter Position Title Here> <Enter Org/Code Here>	Date
--	------	---	------

**LUNAR RECONNAISSANCE ORBITER PROJECT**

**DOCUMENT CHANGE RECORD**

Sheet: 1 of 1

REV LEVEL	DESCRIPTION OF CHANGE	APPROVED BY	DATE APPROVED

CHECK WITH RLEP DATABASE AT:  
<https://lunarngin.gsfc.nasa.gov>  
TO VERIFY THAT THIS IS THE CORRECT VERSION PRIOR TO USE.

## List of TBDs/TBRs

<b>Item No.</b>	<b>Location</b>	<b>Summary</b>	<b>Ind./Org.</b>	<b>Due Date</b>
MRD-039	Radiometric Tracking	LRO and its GDS shall achieve a radiometric Doppler measurement accuracy of less than 8 mm/sec, over a 10 s integration period, with a range accuracy measurement of no more than 15 m. (TBR)	M. Houghton	8/15/05
MRD-040	High Accuracy Tracking	LRO shall support 10 cm, 1 sec average, tracking for a minimum average of 5 hours/day. (TBR)	M. Houghton	8/15/05
MRD-052	Sun Avoidance	LRO shall avoid slewing instrument solar fields of regard through the sun at less than 0.1 deg/s. (TBR)	M. Houghton	8/15/05
MRD-157	Clock Stability	The orbiter clock shall be sufficiently stable over the duration of a LOLA laser pulse time of flight. (TBR)	M. Houghton	8/15/05

**TABLE OF CONTENTS**

	<u>Page</u>
<b><u>1.0</u></b> <b><u>INTRODUCTION</u></b> .....	<b>1-1</b>
<u>1.1</u> <u>Lunar Reconnaissance Orbiter Overview</u> .....	1-1
<b><u>2.0</u></b> <b><u>DOCUMENTS</u></b> .....	<b>2-1</b>
<u>2.1.1</u> <u>Applicable Documents</u> .....	2-1
<u>2.1.2</u> <u>Reference Documents</u> .....	2-3
<u>2.2</u> <u>Definitions</u> .....	2-4
<b><u>3.0</u></b> <b><u>Mission Requirements</u></b> .....	<b>3-1</b>
<u>3.1</u> <u>Mission Derived Requirements</u> .....	3-2
<u>3.1.1</u> <u>Mission Design</u> .....	3-2
<u>3.1.2</u> <u>Launch Vehicle</u> .....	3-4
<u>3.1.3</u> <u>Accommodation</u> .....	3-5
<u>3.1.4</u> <u>Mission Success</u> .....	3-8
<u>3.2</u> <u>Instrument Requirements (LEVEL 2'S)</u> .....	3-9
<u>3.3</u> <u>Spacecraft Requirements (level 2's)</u> .....	3-10
<u>3.3.1</u> <u>Mechanical</u> .....	3-10
<u>3.3.2</u> <u>Thermal</u> .....	3-11
<u>3.3.3</u> <u>GN&amp;C</u> .....	3-12
<u>3.3.4</u> <u>Power</u> .....	3-14
<u>3.3.5</u> <u>C&amp;DH System</u> .....	3-15
<u>3.3.6</u> <u>Comm</u> .....	3-16
<u>3.3.7</u> <u>Flight Software</u> .....	3-17
<u>3.4</u> <u>Ground System Requirements (Level 2's)</u> .....	3-18
<u>3.4.1</u> <u>General Ground System</u> .....	3-18
<u>3.4.2</u> <u>Mission Ops Center</u> .....	3-18
<u>3.4.3</u> <u>Flight Dynamics</u> .....	3-19
<u>3.4.4</u> <u>Ground Network</u> .....	3-20
<u>3.4.5</u> <u>Data &amp; Voice Networks</u> .....	3-20
<b><u>4.0</u></b> <b><u>Qualification Assurance provisions</u></b> .....	<b>4-1</b>
<u>4.1</u> <u>General</u> .....	4-1
<u>4.1.1</u> <u>Analysis</u> .....	4-1
<u>4.1.2</u> <u>Demonstration</u> .....	4-2
<u>4.1.3</u> <u>Inspection</u> .....	4-2
<u>4.1.4</u> <u>Test</u> .....	4-2
<u>4.2</u> <u>Verification Matrix Table</u> .....	4-3
<b><u>Appendix A. Abbreviations and Acronyms</u></b> .....	<b>1</b>



**LIST OF FIGURES**

Figure Page

[INSERT AUTOMATIC LIST OF FIGURES BY CLICKING ON “INSERT INDEX AND TABLES” THEN “TABLE OF FIGURES”. SELECT CAPTION LABEL “FIGURE” AND THEN “OK”

[Figure 3-1. Sample Figure Title Format](#) ..... **Error! Bookmark not defined.**

**LIST OF TABLES**

Table Page

[Table 4-1. Verification Matrix Table](#) ..... 4-4

## **1.0 INTRODUCTION**

This document defines the LRO Mission Level Requirements and flows down directly from the Level 1 NASA Headquarters requirements document ESMD-RLEO-0010.

The Lunar Reconnaissance Orbiter (LRO) mission objective is to conduct investigations that will be specifically targeted to characterize future lunar landing sites and identify potential resources in support of the National Aeronautics and Space Administration's (NASA) Exploration Initiative.

### **1.1 LUNAR RECONNAISSANCE ORBITER OVERVIEW**

The LRO mission will be launched from the Kennedy Space Center (KSC) on a Delta II class Expendable Launch Vehicle (ELV) into a low altitude parking orbit and then injected into a lunar trajectory by the ELV's second or third stage. After a trans-lunar trajectory phase of approximately 100 hours the SC will be inserted into lunar orbit using the on-board propulsion system. The primary mission will be conducted in a circular polar mapping orbit with an altitude of 30-50 kilometers (km) for one earth year. The 3-axis stabilized SC will fly a nadir-pointing attitude with off-nadir maneuvers if required by the observing instruments.

## **2.0 DOCUMENTS**

Enter Text Here

### **2.1.1 Applicable Documents**

431-PLAN-000002	LRO Project Plan
430-PG-1410.2.1	LRO Configuration Management Plan
GPR-7120.5A	GSFC System Engineering GPR
NPR 8000.4	NASA Risk Classification NPR
GSFC-STD-1000	Rules for the Design, Development, Verification, and Operations of Flight System
GSFC-STD-7000	GEVS
430-RQMT-000006	RLEP Mission Assurance Requirements Document
431-PLAN-000005	LRO Systems Engineering Management Plan
431-SPEC-000112	LRO Technical Resource Allocation Specification
431-OPS-000042	LRO Mission Concept of Operations
431-PLAN-000131	LRO Spacecraft PAIP
ESMD-RLEP-0010	LRO Requirements
431-PLAN-000110	LRO Contamination Control Plan
431-SPEC-000016	LRO Electrical Power Subsystem Spec
431-ICD-000018	LRO Power Subsystem Electronics Electrical Interface Control Document
ECSS-E-50-12-A	Space Engineering: SpaceWire – Links, Nodes, Routers and Networks
431-SPEC-000103	LRO SpaceWire Specification
431-SPEC-000102	LRO 1553 Bus Specification
431-ANYS-000010	Radiation Analysis for the Lunar Reconnaissance Orbiter
431-RQMT-000045	Radiation Requirements for the Lunar Reconnaissance Orbiter
431-SPEC-000091	Lunar Reconnaissance Orbiter General Thermal Subsystem Specification

2-1

431-RQMT-000092	Lunar Reconnaissance Thermal Math Model Requirements
431-SPEC-000012	LRO Mechanical Systems Specification
431-RQMT-000113	LRO Pointing and Alignment Specification
431-PROP-000017	LRO Propulsion Subsystem SOW and Specification
MDC 00H0016	Delta II Payload Planners Guide
N/A (ELV Doc.)	LRO ELV Mission Specification
CCSDS 727.0-B-2	CCSDS File Delivery Protocol (CFDP): Blue Book
CCSDS 701.0-B-3	Advanced Orbiting Systems, Networks and Data Links: Architectural Specifications
CCSDS 102.0-B-5	Packet Telemetry
NPD 2810.1	NPD – Security of Information Technology
431-RQMT-000048	LRO Detailed Mission Requirements for LRO Ground System
430-PROP-000001	Lunar Reconnaissance Orbiter Payload Proposal Information Package (PIP)
431-ICD-000049	LRO Ground Data System Interface Control Document
431-ICD-000085	CRaTER Mechanical Interface Control Document
431-ICD-000086	DLRE Mechanical Interface Control Document
431-ICD-000087	LAMP Mechanical Interface Control Document
431-ICD-000088	LEND Mechanical Interface Control Document
431-ICD-000089	LOLA Mechanical Interface Control Document
431-ICD-000090	LROC Mechanical Interface Control Document
431-ICD-000094	CRaTER Electrical Interface Control Document
431-ICD-000095	DRLE Electrical Interface Control Document
431-ICD-000096	LAMP Electrical Interface Control Document
431-ICD-000097	LEND Electrical Interface Control Document
431-ICD-000098	LOLA Electrical Interface Control Document

431-ICD-000099	LROC Electrical Interface Control Document
431-ICD-000104	CRaTER Data Interface Control Document
431-ICD-000105	DRLE Data Interface Control Document
431-ICD-000106	LAMP Data Interface Control Document
431-ICD-000107	LEND Data Interface Control Document
431-ICD-000108	LOLA Data Interface Control Document
431-ICD-000109	LROC Data Interface Control Document
431-ICD-000114	LROC Thermal Interface Control Document
431-ICD-000115	LAMP Thermal Interface Control Document
431-ICD-000116	Diviner Thermal Interface Control Document
431-ICD-000117	LOLA Thermal Interface Control Document
431-ICD-000118	CRaTER Thermal Interface Control Document
431-ICD-000119	LEND Thermal Interface Control Document
431-PLAN-000100	LRO I&T Plan
431-PLAN-000101	LRO Observatory Plan

### **2.1.2 Reference Documents**

LRO Library Document      Master Equipment List

## 2.2 DEFINITIONS

Throughout this document, the term Orbiter (or LRO Orbiter) will be defined as the LRO Spacecraft and LRO Payload.

Throughout this document, the term Spacecraft (or LRO Spacecraft) will be defined as the Spacecraft Bus, Solar Array System and High Gain Antenna System.

Throughout this document, the term Payload (or LRO Payload) will be used to describe the instrument suite consisting of CRaTER, Diviner, LAMP, LEND, LOLA, LROC and the technical demonstration payload of opportunity, Mini-RF.

Throughout this document, Spacecraft Bus (or LRO Spacecraft Bus) will be defined as the Propulsion module and Instrument Module.

Instrument - Suite of 6 instruments selected and technical demonstration payload of opportunity

**Component:** A component is a self-contained combination of items performing a function. Examples are electronic box, transmitter, gyro package, motor, and battery. For the purposes of this document, the term component is used generically to represent an analyzable or testable level of assembly below the observatory level.

**Subsystem:** A functional subdivision consisting of two or more components. Science instruments and experiments are considered subsystems.

System

Mission

Ground Segment

Space Segment

Launch Segment

### **3.0 MISSION REQUIREMENTS**

In this document, a requirement is identified by “shall,” a good practice by “should”, permission by “may”, or “can”, expectation by “will”, and descriptive material by “is.”

<Requirements reside in this section. The following are the bookmarks shown in Section 3.1 are to be used in requirement type documents that will be entered in DOORS.>

**PLACEHOLDER FOR REQUIREMENTS FLOW DIAGRAM  
WITH SUPPORTING TEXT**

**3.1 MISSION DERIVED REQUIREMENTS****3.1.1 Mission Design**

Req.#	Title	Requirement	Rationale
MRD-001	Launch Mass	LRO's launch mass shall not exceed 1480 kg.	Upper end of Delta II performance, assuming 9.5 ft fairing, 5 kg yo-yo, and direct transfer.
MRD-002	Launch Vehicle	LRO shall be designed to fly on a Delta II 2925H, with a 9.5 ft fairing.	Tied to Launch Mass. If changed, Launch Mass must be reassessed.
MRD-003	Launch Trajectory	LRO shall utilize a direct lunar transfer trajectory.	Provides adequate performance while minimizing transfer time and complexity.
MRD-004	Launch Window	The LRO launch window shall be constrained such that its nominal spin vector at separation is within 15 deg of either the sun or anti-sun.	Protects against immediate sun exposure down the instrument boresights (assumes instruments are perpendicular to spin axis).
MRD-005	Propulsive Despin	LRO shall have the ability to despin autonomously, propulsively, from rates as high as 5 rpm, one axis, at LV separation.	Needed in case residual momentum exceeds momentum storage capability (LV yo-yo failure, for example). Must avoid flat spin to ensure sun avoidance on instruments.
MRD-006	Non-Propulsive Ops	LRO shall have the ability to handle body rates of at least 2 deg/s, per axis, without firing thrusters.	Gives reasonable chance of avoiding early (autonomous) thruster firings.
MRD-007	Deployables	LRO's deployables shall be capable of deploying with body rates as high as 2 deg/s, per axis.	Would like to deploy the array, for example, as soon as possible after LV separation.
MRD-008	Sun Pointing	The LRO design shall be capable of putting the observatory into a known orientation with respect to the sun without knowing its inertial position.	Provides for sun pointing without the need for a valid ephemeris or inertial sensors.
MRD-009	Inertial Pointing	The LRO design shall be capable of putting the observatory into a known orientation with respect to inertial space.	Needed, first, for course corrections, but also, later, for instrument calibrations, etc.
MRD-010	Propulsive Maneuvers	LRO shall have the ability to do course corrections, lunar orbit insertion, station-keeping, and momentum management using an onboard propulsion system.	Onboard propulsion is required to do any long term lunar mission.



MRD-011	Low Maintenance Orbit	LRO shall make use of a low maintenance orbit for instrument commissioning.	Conserves fuel prior to nominal mission. Same orbit may be used for extended mission.
MRD-012	Mission Orbit	The primary mission shall be conducted in a circular mapping orbit with a nominal altitude of 50 +/- 20 km (altitude is measured to mean lunar surface).	Lowest practical altitude and tolerance given fuel considerations.
MRD-013	Orbit Inclination	The orbit inclination shall be 90 degrees +/- 1 degree.	Poles are of greatest interest, but lunar polar orbits wobble.
MRD-014	Nadir Pointing	The LRO design shall be capable of putting the observatory into a known orientation with respect to the lunar surface.	Will be used for normal operations, including "off-nadir" observations.
MRD-015	Solar Array Tracking	LRO shall be capable of pointing its solar array at the sun while maintaining a lunar referenced orientation.	Must be power positive during normal ops.
MRD-016	Antenna Tracking	LRO shall be capable of pointing its HGA to Earth ground stations while maintaining a lunar referenced orientation.	Must be able to simultaneously take and send data.
MRD-017	Momentum Management	LRO shall be capable of going at least 2 weeks (goal of 4) without a momentum management maneuver.	Plan to do all maneuvers within view of Earth. Goal is to minimize impact on science.
MRD-018	Yaw Maneuvers	Twice a year, LRO shall perform a 180 deg yaw maneuver, reversing its direction of flight.	Must be done to keep the sun on the correct (solar array) side of the spacecraft.
MRD-019	Lunar Eclipses	LRO shall be capable of withstanding a worst case lunar eclipse (160 min), twice a year, on average.	Lunar eclipses will occur throughout the mission. Some form of hibernation is acceptable.
MRD-020	Spacecraft Safing	LRO shall be designed to detect faults and autonomously move to progressively simpler control states, shed loads, etc., in response to status telemetry from S/C subsystems.	Some form of fault detection/correction must be implemented to increase probability of mission success. Power, attitude, and ground comm. are critical.
MRD-021	Mission Duration	LRO shall be designed to have a minimum mission duration of 14 months.	Predicted 2 month commissioning phase plus minimum 12 month mapping mission.

MRD-022	Extended Mission	LRO shall carry sufficient consumables to allow for a 4 year extended mission in a low maintenance orbit.	It may be desirable to use LRO as a communication relay for subsequent RLEP mission, or, alternatively, to continue primary observations beyond the baseline mission. Additional design augmentations may be made, on a case-by-case basis, to bolster the probability of having a successful extended mission.
MRD-023	End of Mission	LRO's mission will be terminated in a manner that meets NASA Planetary Protection Requirements as stated in NPD 8020.7F	LRO Mission is Category 1 based on NPR 8020.12C, section A.1.

### 3.1.2 Launch Vehicle

Req.#	Title	Requirement	Rationale
MRD-024	Vehicle Performance	The launch vehicle must be capable of delivering a 1480 kg payload to a trajectory with a $C_3 > -1.85$	Provides boundary conditions for Flight Dynamics and Propulsion for Trans Lunar Injection (TLI). Bounds S/C launch mass.
MRD-025	Insertion Accuracy	TLI accuracy at orbiter separation from the LV third stage shall be within $\pm 3$ m/sec (3-sigma) of target inertial velocity.	TLI injection errors will be corrected by spacecraft at MCC1. Above requirement is allocated in dV budget.
MRD-026	De-Spin	The LV shall despin LRO to a rate $< 2$ rpm.	Provides some chance of being able to avoid early (autonomous) thruster firings.
MRD-027	Tip Off rates	The LV induced tip-off rates shall be $< 2$ deg/sec ( $3\sigma$ ), in the transverse axes, at separation.	Assume LV has de-spun Orbiter to approximately zero rate prior to separation. Low tip off rates required to assure tip off capture by wheels.
MRD-028	Vehicle Interfaces	LRO shall be compatible with all LV operations, interfaces, and environments as specified in Delta II Payload Planners Guide and the LRO ELV Mission Specification. In the event of a conflict the Mission Specification takes precedence.	Payload Planners Guide is the generic source of Delta II performance and interface data, the Mission Specification is the standard Boeing format ICD between the Orbiter and the ELV.

**3.1.3 Accommodation**

Req.#	Title	Requirement	Rationale
MRD-029	Mass Allocations	Subsystems/instruments shall not exceed the mass allocations given in the LRO Technical Resource Allocations Spec 431-SPEC-000112.	Mass budget is managed in the LRO Technical Resource Allocations Spec.
MRD-030	Mechanical Interfaces	Subsystems/instruments shall comply with the LRO Mechanical System Spec 431-SPEC-000012.	All mechanical interfaces must be managed and coordinated to ensure mission success.
MRD-031	Power Allocations	Subsystems/instruments shall not exceed the power allocations given in the LRO Technical Resource Allocations Spec 431-SPEC-000112.	Power budget is managed in the LRO Technical Resource Allocations Spec.
MRD-032	Operating Voltage	Subsystems/instruments shall operate nominally at 21-35 VDC.	Power system will nominally output 22-35 VDC. This gives an appropriate cushion to allow for line losses.
MRD-033	Electrical Interfaces	Subsystems/instruments shall comply with the LRO Electrical System Spec 431-SPEC-000008.	All electrical interfaces must be managed and coordinated to ensure mission success. This includes grounding, magnetics, charging, etc.
MRD-034	Thermal Interfaces	Subsystems/instruments shall comply with the LRO Thermal System Spec 431-SPEC-000091.	All thermal interfaces must be managed and coordinated to ensure mission success.
MRD-035	Low-Rate Data	LRO shall utilize a MIL-STD-1553B network per 431-SPEC-000008 for telemetry and control < 300 kbps.	Industry standard interfaces simplify instrument interfaces, improve flexibility and support future growth
MRD-036	High-Rate Data	LRO shall use SpaceWire (ECSS-E-50-12A) per 431-SPEC-000103 for telemetry and control > 300 kbps.	Industry standard interfaces simplify instrument interfaces, improve flexibility and support future growth
MRD-155	Real-Time Data	LRO shall collect and send real-time, housekeeping data to the ground.	Real-time HK data is needed to monitor and control the observatory.
MRD-037	Data Storage	LRO shall have the ability to store at least 17.5 hours worth of data.	Based on the assumption that bulk data will be transmitted to 1 station.
MRD-038	Data Transfer	LRO and its Ground System shall be capable of transferring 24 hrs worth of data to the ground in 6.5 hours.	Based on the assumption that bulk data will be transmitted to 1 station.

MRD-039	Radiometric Tracking	LRO and its GDS shall achieve a radiometric Doppler measurement accuracy of less than 8 mm/sec, over a 10 s integration period, with a range accuracy measurement of no more than 15 m. (TBR)	Sufficient to meet LRO's orbit determination requirements.
MRD-040	High Accuracy Tracking	LRO shall support 10 cm, 1 sec average, tracking for a minimum average of 5 hours/day. (TBR)	In order to support the Level 1 requirement for geodetic grid, some higher accuracy tracking is required.
MRE-041	Orbit Determination	LRO shall have a minimum Orbit Determination Accuracy of 500/18m (Total Position RMS/Radial RMS), 1-sigma, post-processed.	Knowledge assuming LP100K gravity model and existing S-band RF tracking capabilities.
MRD-042	Time Knowledge	The Orbiter and ground system shall provide knowledge of the Orbiter time with respect to UTC to an accuracy of 3 ms.	Meets LOLA reconstruction requirement.
MRD-043	Time Maintenance	Orbiter time shall be maintained to within 100 ms of UTC at all times.	Allows instrument stored commands to go off within 100 ms of desired time.
MRD-157	Clock Stability	The orbiter clock shall be sufficiently stable over the duration of a LOLA laser pulse time of flight. (TBR)	To meet the range accuracy of each LOLA measurement.
MRD-044	-	Deleted	-
MRD-045	-	Deleted	-
MRD-046	-	Deleted	-
MRD-047	-	Deleted	-
MRD-048	-	Deleted	-
MRD-049	Pointing Allocations	Subsystems/instruments shall meet all pointing-related allocations given in the LRO Pointing and Alignment Specification 431-SPEC-000113.	All pointing and alignment budgets (including solar array and high gain antenna) are managed in the LRO Pointing and Alignment Spec.

MRD-050	Mission Phases	LRO and its mission elements shall be designed to support all mission phases defined in the LRO Mission Ops Concept Doc. 431-OPS-000042.	The operations concept is captured in the Mission Ops Concept Document and drives numerous design aspects.
MRD-051	Continuous Operations	LRO and its Ground System shall be designed to support continuous operations during the primary mission, except for planned outages for momentum and orbit adjusts, and instrument calibrations.	Ensures the maximum data return.
MRD-156	Lights-Out Operations	LRO shall be capable of operating normally for at least 72 hrs between command loads.	Allows for unmanned operations over a 3-day weekend.
MRD-052	Sun Avoidance	LRO shall avoid slewing instrument solar fields of regard through the sun at less than 0.1 deg/s. (TBR)	Instrument solar fields of regard encompass instrument fields of view. Rate is driven by LOLA and LROC.
MRD-099	Power Negative Ops	All power negative operations shall be limited such that the battery depth of discharge does not exceed 30%.	Avoids battery degradation caused by repeated deep discharge.
MRD-100	Thermally Off-Nominal Ops	All off-nominal operations shall be limited such that component temps can be maintained within set limits.	Avoids damage caused by inadvertent heating or cooling of S/C components. Thermal limits includes gradients.
MRD-053	Maneuver Notification	LRO shall safe the instruments, as required, prior to any off-nominal operations (including maneuvers).	In general, maneuvers will require off-nadir pointing. May be contamination concern.
MRD-054	Data Loss	LRO and its mission elements shall adhere to the Data Loss Allocations given in the LRO Technical Resource Allocations Spec 431-SPEC-000112.	Data loss budget is managed in the Technical Resource Allocations Spec.
MRD-055	Data Product Delivery	The mission shall deliver all data products specified in the LRO Level 1 requirements to the Planetary Data System for archiving and distribution.	The PDS is the final clearing house for all LRO measurement data.
MRD-056	Information Assurance	LRO and its ground system shall provide Information Assurance in compliance with NASA policies, specifically NPD 2810.	Provides direction designed to ensure that safeguards for the protection of the integrity, availability, and confidentiality of IT resources (e.g., data, information, applications, and systems) are integrated into and support the missions of NASA.

**3.1.4 Mission Success**

<b>Req.#</b>	<b>Title</b>	<b>Requirement</b>	<b>Rationale</b>
MRD-057	Risk Classification	LRO shall meet the NPR8705.4 Appendix B requirements for Class C payloads with the exception of Test Program and EEE Parts requirements which shall meet the requirements for Class B payloads	The modified Class C classification is consistent with and appropriate for the cost/schedule constraints established when the mission was defined.
MRD-058	Mission Assurance	The LRO mission shall meet the S&MA requirements in the RLEP MAR 430-RQMT-000006.	Mission Assurance aspects are handled in the Mission Assurance Requirements Document.
MRD-059	Configuration Control	LRO configuration shall be controlled in accordance with the RLEP CM Plan 430-PG-1410.2.1.	Configuration Management aspects are handled in the Configuration Management Plan.
MRD-060	Requirements Control	Derived subsystem requirements and specifications, to the component level, require the review & approval of the LRO Mission Systems Engineer or designate.	Ensures a cohesive set of requirements throughout the mission.
MRD-061	Margins/Reserves	Technical margins and reserves shall be maintained per the LRO Systems Engineering Management Plan (SEMP) 431-PLAN-000005.	Management of margins and reserves is critical to mission success.
MRD-062	Coordinate Systems	All subsystems and instruments must reference the common coordinate system defined by the thrust direction (+X), the nadir viewing deck (+Z) and the right hand rule (+Y).	This will aid in clear, concise communication between subsystems and with instrument providers.
MRD-063	Units Policy	All LRO subsystems and Instruments shall adhere to the units policy given in LRO SEMP 431-PLAN-000005.	Addresses the need to plan for and prevent the misapplication of English and Metric units in all aspects of mission development & operations.
MRD-064	Verification Testing	LRO shall undergo verification testing in accordance with the LRO Verification Plan 431-PLAN-000101.	Per Mission Assurance Requirements Document.
MRD-065	Mechanical Environments	The orbiter shall function nominally within the mechanical environments of the mission as specified in LRO Mechanical Systems Specification 431-SPEC-000012.	Derived from Delta II enveloping case to include Atlas V considerations and covers all mission phases per Ops Concept Document.

MRD-066	Electrical Environments	The orbiter shall function nominally within the electrical environments of the mission as specified in the LRO Electrical Systems Specification 431-SPEC-000008.	Covers electrical environments for all mission phases.
MRD-067	Thermal Environments	The orbiter shall function nominally within the thermal environments of the mission as specified in the LRO Thermal Systems Specification 431-SPEC-000091.	Provides temperature predicts for all components and environments for all mission phases.
MRD-068	Radiation Environments	All subsystems shall meet the requirements given in the LRO Radiation Requirements Doc 431-RQMT-00045.	Provides details on the radiation environment and planned mitigation, including EEE parts selection.
MRD-069	Contamination Control	Acceptable contamination levels shall be maintained on the Orbiter and its subsystems, at all times, per the LRO Contamination Control Plan 431-PLAN-000110.	Particulate & molecular contaminants can limit functional life of components (solar arrays, UV instruments, etc.).

### 3.2 INSTRUMENT REQUIREMENTS (LEVEL 2'S)

- REMOVED TO INSTRUMENT REQUIREMENTS DOCUMENTS -

**3.3 SPACECRAFT REQUIREMENTS (LEVEL 2'S)****3.3.1 Mechanical**

Req.#	Title	Requirement	Rationale
MRD-070	Structural Stability	The LRO structure shall provide a stable mounting surface and alignment platform for all subsystem components and instruments that meets mission pointing requirements per the LRO Pointing and Alignment Specification 431-SPEC-000113.	The structure is an integral part of the overall pointing budget.
MRD-071	Fields of View	The LRO structure shall provide clear FOVs for all components/instruments as required by their MICDs.	Many components and all instruments require a FOV external to the S/C.
MRD-072	Flexible Modes	The LRO structure shall be sufficiently stiff to avoid excitation by the attitude control system or any other moving parts on the spacecraft.	Care must be taken to ensure that structure's lowest frequency mode is outside the controller bandwidth (typically at least 1 decade above).
MRD-073	Accessibility	The LRO structure shall provide access to components/instruments, as needed, for GSE and test while integrated to the S/C.	It will be necessary to test and calibrate several components at various stages of development.
MRD-074	Disturbance Torques	All mechanism torques (disturbances) shall be managed or limited so as to prevent interference with spacecraft pointing requirements.	Torque disturbances must be managed so that pointing requirements can be met.
MRD-075	Mass Properties	LRO mass properties (including CG migration) shall be managed in such a way so as to prevent interference with spacecraft control requirements.	Momentum build-up at the moon and weight shift due to fuel usage will have significant impacts on the LRO design.
MRD-076	Support Equipment	LRO mechanical ground support equipment shall be provided for I&T, hoisting, transportation, etc.	MGSE will be needed at various stages of LRO development, including launch site operations.
MRD-077	Mechanical Surrogates	LRO shall make use of mass simulators, baseplates, and wiring mock-ups (etc.), as appropriate.	This will help to ensure proper structural and interface compliance.



**3.3.2 Thermal**

Req.#	Title	Requirement	Rationale
MRD-078	Operational Ranges	The LRO thermal control system shall maintain all component and structural interface temperatures to be within their appropriate limits during normal operations as specified in the Thermal Systems Specification 431-SPEC-000091.	Must maintain proper temperature ranges to ensure functionality of all components and instruments.
MRD-079	Survival Ranges	The LRO thermal control system shall maintain all component and structural interface temperatures to be within their survival limits during all phases of the mission as specified in the Thermal Systems Specification 431-SPEC-000091.	Must maintain proper temperature ranges to avoid damaging any component/instrument.
MRD-080	Minimum Bus Voltage	The LRO survival heaters shall be sized for a minimum bus voltage of 24V.	Based on minimum bus voltage out of eclipse due to 1 battery cell failure.
MRD-081	Monitoring	LRO shall monitor temperature sensors for all components and critical structural elements.	Must have knowledge of LRO temperatures to aid in post-processing and/or troubleshooting.
MRD-082	Ground Support	LRO thermal GSE shall be provided to support I&T, transportation, etc., as required by the ground flow.	TGSE will be needed at various stages of LRO development, including launch site operations.
MRD-083	Thermal Simulators	Thermal simulators shall be used in verifying performance of systems during orbiter level testing.	Orbiter level testing must be done in space-like environments to ensure mission success.

**3.3.3 GN&C**

Req.#	Title	Requirement	Rationale
MRD-084	Attitude Control System	The attitude control system shall maintain LRO's orientation, as well as that of its solar array and high gain antenna, throughout the mission.	LRO's orientation must be carefully controlled throughout the mission to maintain the integrity of all systems and to meet mission objectives.
MRD-085	ACS Hardware	The ACS sensors and actuators shall be controlled via the Low Speed Bus.	Utilizing simplest possible interfaces increases system reliability.
MRD-086	ACS Software	The ACS software shall be hosted on the LRO Single Board Computer.	Sharing the abundant resources of the SBC significantly reduces avionics costs/complexity.
MRD-087	Propulsion Control	The GN&C subsystem shall control and monitor the propulsion system.	The propulsion system is part of the GN&C subsystem.
MRD-088	Initial Stabilization	The GN&C subsystem shall autonomously stabilize the orbiter after separation from the LV.	Must avoid flat spin to ensure sun avoidance on instruments, etc.
MRD-089	Sun Pointing Latency	The ACS shall maneuver LRO from any orientation to a power positive one within 10 min of initialization.	This mode is nominally only entered when it is imperative that the sun be put on the solar array.
MRD-090	Sun Pointing Accuracy	When sun pointing, the ACS shall put the sun within 15 deg of the specified position.	This angle is sufficient to ensure that enough sun gets onto the solar array.
MRD-091	Default Mode	The ACS default mode shall put the sun within 15 deg of a specified position.	In the event of an anomaly, this is the safest orientation for the S/C to be put into.
MRD-092	Thrust Pointing	The ACS shall hold pointing to within 5 deg of the desired orientation during thruster operations.	Pointing must be maintained to ensure that the resultant thrust is in the desired direction.
MRD-093	Delta-V Budget	The detailed Delta-V budget shall be documented in the LRO Technical Resource Allocations Specification 431-SPEC-000112.	Flight Dynamics determines the fuel requirements in terms of Delta-V.
MRD-094	Fuel Budget	The detailed propellant budget shall be documented in the LRO Technical Resource Allocations Specification 431-SPEC-000112.	The actual fuel budget factors in all subsequent effects (cosine losses, residual fuel, etc.).

MRD-095	Minimum Thrust	The propulsion system shall be capable of producing 140 N of thrust, in such a way that allows for lunar capture, with backup, as determined by Flight Dynamics.	Minimum thrust required for lunar capture. Without it, LRO can't brake at the moon.
MRD-096	Thruster Locations	The LRO thrusters shall be configured such that they provide the necessary control authorities (thrust and torque) without impinging upon any S/C structure or components.	Impingements can cause unwanted forces and torques, as well as heating issues.
MRD-097	Momentum Management	The GN&C subsystem shall be capable of adjusting momentum within 1 N-m-s of a desired set-point.	Momentum management is critical for lunar missions due to lack of magnetic field (i.e. continuous capability).

**3.3.4 Power**

Req.#	Title	Requirement	Rationale
MRD-098	Power Distribution	The power system shall distribute primary power to the subsystems as required by their EICDs.	Power architecture shall be used to supply over-current protected power to all the loads.
MRD-101	Voltage Supply	The power system shall provide unregulated 22-35 VDC power at all the power supply outputs.	Subsystems/instruments shall operate nominally at 21-35 VDC. This gives an appropriate margin for line losses.
MRD-102	Launch & Early Ops	The battery shall be able to support the S/C during launch operations and until a power positive condition has been achieved.	LRO will require a certain size battery (A-Hr). It must be enough to support all mission phases.
MRD-103	Nominal Operations	The power system shall be designed to support full mission load of 823 W (orbit average) after 14 months.	Provides sufficient margin beyond the allocated/predicted load demands.
MRD-104	Minimum Load	The power system shall carry a minimum load of 180 W whenever the solar array is illuminated.	Insures compliance with voltage specifications.
MRD-105	Peak Power	The power system shall be capable of supporting a 1500 W peak power load for up to 5 minutes.	The power system must be able to handle the peak power load.
MRD-106	Switched Power	Switched power services shall have re-settable over-current protection.	Power system protection.
MRD-107	Switched Cutoffs	The power system shall switch off any switched service that exceeds its max sustainable current, and keep it off until commanded otherwise.	To protect the power services.

**3.3.5 C&DH System**

Req.#	Title	Requirement	Rationale
MRD-108	Processing Platform	The C&DH Single Board Computer shall provide an adequate processing platform for the execution of all Flight Software, including ACS Flight Software.	C&DH and GN&C flight software require significant processor resources.
MRD-109	Bus Controller	The C&DH Single Board Computer shall operate as the Bus Controller for the 1553 network.	Mechanism for redundant configurations to prevent two simultaneous BCs.
MRD-110	Data Protocols	The C&DH shall support CCSDS telecommand, telemetry, and CFDP.	Standard protocols used by flight and ground data and comm. systems.
MRD-111	Hardware Decoding	The C&DH shall support hardware decoding of critical commands	Method for recovery from anomalous conditions.
MRD-112	Telemetry Encoding	The C&DH shall support telemetry encoding.	The LRO communications scheme will likely utilize telemetry encoding.
MRD-113	Hardline Interface	The C&DH shall provide hardline interface(s) for use in ground testing, through spacecraft umbilical.	Needed throughout I&T and at the launch site.
MRD-114	Mission Time Counter	The C&DH shall provide a Mission Elapsed Time (MET) counter with a resolution of 1 sec, which cannot be adjusted, and is capable of operating for 5 years without rolling over.	MET shall always increment and never be adjusted to provide unambiguous time reference.
MRD-115	Pulse Per Second	The C&DH shall provide a 1Hz pulse as required by the instruments.	Mechanism for synchronizing operations, and time-tagging data.
MRD-116	Time Messages	The C&DH shall generate an Orbiter Time of Pulse message for each instrument as required.	Mechanism for synchronizing operations, and time-tagging data.
MRD-117	LAMP Interface	The C&DH shall support LAMP's heritage serial interfaces, as defined in LAMP's EICD.	Acceptance of existing interfaces simplified instrument development with little cost to S/C.
MRD-118	Backup H/K Storage	The C&DH SBC shall be capable of storing 2 hours of H/K data.	Covers periods when the mass storage device is unavailable.
MRD-125	Comm. Relay Capability	The C&DH shall provide an interface for a potential comm. relay.	It may be desirable to operate LRO as a comm. relay in extended mission.

**3.3.6 Comm**

Req.#	Title	Requirement	Rationale
MRD-119	Operational TT&C	LRO shall provide communication to support operational mission telemetry, tracking and command.	TLM / CMD is required to support LRO operations.
MRD-120	TLM/CMD Links	LRO Shall provide command and telemetry links to support TLM / CMD functions.	Bidirectional communication is required to support LRO's operations concept.
MRD-121	Radiometrics	LRO shall provide radiometric tracking capabilities.	The LRO Flight Dynamics Team requires range and range-rate measurement to determine LRO's orbit.
MRD-122	Command Link	LRO shall provide a 4 kbps forward communication link, operating in the Near-Earth S-Band, with a bit error rate of not greater than $1 \times 10^{-5}$ , and a design link margin of not less than 3 dB, to support vehicle commanding.	This is a sufficient command link required to support LRO operations.
MRD-123	Telemetry Downlink	LRO shall provide a 2.186 Mbps return communication downlink, operating in the Near-Earth S-Band, with a bit error rate of not greater than $1 \times 10^{-9}$ , and a design link margin of not less than 3 dB, to support vehicle operational telemetry.	This is a sufficient telemetry link required to support LRO operations.
MRD-124	High Rate Downlink	LRO shall provide a 100 Mbps return communication downlink, operating in the Near-Earth Ka-Band, with a bit error rate of not greater than $1 \times 10^{-9}$ , and a design link margin of not less than 3 dB, to support mission science offload.	This is a sufficient high rate link required to support LRO operations.
MRD-126	Concurrent Downlink	The LRO mission communication system shall support the simultaneous downlink of operational TT&C and high rate mission data.	LRO requires near-continuous TT&C while in view of the LRO ground system. LRO's CFDP high rate downlink protocol requires a command uplink to transmit file ACK/NAK indicators to the spacecraft.

**3.3.7 Flight Software**

<b>Req.#</b>	<b>Title</b>	<b>Requirement</b>	<b>Rationale</b>
MRD-127	Software Initialization	The flight software shall initialize and support operations without the need of an upload from the ground.	Essential aspect of LRO operations.
MRD-128	Reprogrammability	The flight software shall be reprogrammable during flight	Allow correction of SW errors or adding new SW features post-launch.
MRD-129	Processor Utilization	The flight software shall be bound by the processor margins found in table 3.07-1 of the GSFC Rules for Design, GSFC-STD-1000	Allow room to add software functions post-launch.
MRD-130	Software Organization	The flight software shall be organized such that functional units of code can be modified on orbit in modular form.	Ease of management of configuration settings.
MRD-131	Absolute Time Sequence	The flight software shall support the execution of stored command sequences that can be triggered at an absolute UTC time with 1 second resolution time tags.	Essential aspect of LRO operations.
MRD-132	Relative Time Sequence	The flight software shall support the execution of stored command sequences that can be triggered at a time relative to another event with 1 second resolution.	Essential aspect of LRO operations.
MRD-133	Telemetry Monitoring	The flight software shall support monitoring of any telemetry point and initiate stored command in response to pre-defined conditions.	Flexibility is necessary to support autonomous error recovery conditions that may not be known until after launch.
MRD-134	Diagnostic Tlm Support	To allow ground diagnosis of in-flight anomalies, the flight software shall accept ground commands to run on-board diagnostics and report the results in telemetry	Flexibility is necessary to support debugging conditions that may not be known until after launch.
MRD-135	File Management	The flight software shall provide commands to allow operators to manage the on-board file systems (directory listing, and file move/copy/delete).	Need the ability to clean up unused files before the file system fills up.

**3.4 GROUND SYSTEM REQUIREMENTS (LEVEL 2'S)****3.4.1 General Ground System**

Req.#	Title	Requirement	Rationale
MRD-136	System Support	The ground system shall provide ground system capability for supporting all mission phases.	Support pre-launch testing and post-launch operations
MRD-137	Data Delivery	The ground system shall deliver measurement data to the instrument SOCs within 24-hours of ground receipt.	Deliver data in a timely manner for measurement data processing. Ensures ground can deliver data without backlog.
MRD-138	Critical Operations	The ground system shall provide essential capabilities to support all critical LRO operations.	Verify health and safety of orbiter. Ensure proper coverage for all critical operations
MRD-139	Testing & Verification	The ground system shall perform and support verification testing, operations testing, and mission rehearsal testing	Ground system and operations verification
MRD-140	Data Protocols	The ground system shall support CCSDS telecommand, telemetry, and CFDP.	Standard protocols used by flight and ground data and comm. systems.

**3.4.2 Mission Ops Center**

Req.#	Title	Requirement	Rationale
MRD-141	Support Functions	The ground system shall provide a dedicated mission operations center that support the following functions: - Mission Planning - Telemetry and Command - Health and Safety - Trending - Data Storage - Data Distribution	Basic operational functions needed for LRO
MRD-142	Center Location	The dedicated MOC shall be located at GSFC.	Available infrastructure reduces development and test schedule



MRD-143	H/K Data Storage	The MOC shall store orbiter housekeeping data for the life of the mission	Needed for anomaly and trend investigations
MRD-144	Command Origination	All commands sent to the orbiter shall originate from the MOC	Security and eliminates the need for command priority
MRD-145	SOC Interfaces	The MOC shall provide interfaces to the instrument SOC's for the following: - Housekeeping data - Measurement data - Mission Products used for planning and data processing - Instrument command sequence/requests	Required for higher level measurement products and basic mission operations

### 3.4.3 Flight Dynamics

Req.#	Title	Requirement	Rationale
MRD-146	Mission Planning	The ground system shall provide trajectory, orbit and maneuver support during all mission phases.	Support planning and measurement processing
MRD-147	Orbit Determination	The ground system shall provide orbit determination support during all mission phases	Support planning and measurement processing
MRD-148	Attitude Determination	The ground system shall provide attitude determination support during all mission phases	Support planning and measurement processing
MRD-149	Mission Products	The ground system flight dynamics systems shall generate the required mission products for mission planning, calibration, and data processing functions	Support planning and measurement processing

**3.4.4 Ground Network**

<b>Req.#</b>	<b>Title</b>	<b>Requirement</b>	<b>Rationale</b>
MRD-150	Ka-Band Services	The ground system shall provide Ka-Band ground services	Support current ConOps
MRD-151	S-Band Services	The ground system shall provide sufficient S-Band Tracking, Telemetry, and Command (TT&C) to support the mission	Support current ConOps
MRD-152	Telemetry & Command	The ground network shall support all telemetry and command modes throughout the mission phases	Support current ConOps

**3.4.5 Data & Voice Networks**

<b>Req.#</b>	<b>Title</b>	<b>Requirement</b>	<b>Rationale</b>
MRD-153	Data Networks	The ground system shall provide all data networks to support the mission from pre-launch through mission disposal	Needed to support mission from pre-launch through mission disposal.
MRD-154	Voice Networks	The ground system shall provide all voice networks to support the mission from pre-launch through mission disposal	Needed to support mission from pre-launch through mission disposal.

## **4.0 QUALIFICATION ASSURANCE PROVISIONS**

### **4.1 GENERAL**

All requirements in this document shall be verified by one of the four methods defined below.

#### **4.1.1 Analysis**

The analysis method is used when:

- A rigorous, representative, and conclusive analysis is possible
- Test is not cost effective, and
- Inspection and demonstrations are not adequate

Analyses may include, but are not limited to, engineering analysis (which includes models and simulations), review of record, and similarity analysis.

##### **4.1.1.1 Engineering Analysis**

Engineering analysis may be quantitative, qualitative, or a combination of the two. Quantitative analysis involves the study and modeling of the physical entity whose performance is to be verified. Examples of quantitative analyses include end-to-end link analysis, structural (static and dynamic) analysis, thermal models, pointing knowledge and stability. Qualitative analyses are non-numerical and related to qualitative measure of performance, such as failure modes and effects analyses (FMEA), maintainability, and redundancy.

##### **4.1.1.2 Validation of Records and Other Documentation Analysis**

This kind of analysis uses design and manufacturing documentation to show compliance of design features and manufacturing processes. Validation of design documentation, e.g., engineering drawings, verifies that the “as-designed” hardware complies with contractual design and construction requirements. Validation of manufacturing records at end-item acceptance verifies that the “as-built” hardware has been fabricated per the approved design and associated documentation. Review and analysis of other documentation such as acceptance data packages and other compliance documentation of lower levels of assembly are valid analysis techniques.

##### **4.1.1.3 Similarity Analysis**

Similarity is included as a valid verification/qualification method. Qualification by similarity is used in lieu of test when it can be shown that an item is similar to, or identical in design to another item that has been previously qualified to equivalent, or more stringent requirements. Formal qualification documentation of the previously qualified item must be available for assessment when planning to qualify by similarity. Furthermore, an item whose design has been qualified by similarity must undergo acceptance verification to assess workmanship.

### **4.1.2 Demonstration**

Demonstration is a verification method that provides a qualitative determination, rather than direct quantitative measurement, of the properties or functional characteristics of an end-item. The qualitative determination is made through observation with, or without test equipment or instrumentation.

### **4.1.3 Inspection**

Inspection is the verification method used to verify construction features, workmanship, dimension, physical characteristics, and spacecraft conditions such as configuration, cleanliness, and locking hardware. Inspection also includes simple measurements such as length, and it is performed without the use of special laboratory or precision equipment. In general, requirements specifying function or performance are not verified by inspection.

### **4.1.4 Test**

Verification by test consists of direct measurement of performance parameters relative to functional, electrical, mechanical, and environmental requirements. These measurements are obtained, during or after controlled application of functional and environmental stimuli to the test article, e.g., payload or satellite, and using instrumentation or special test equipment that is not an integral part of the test article being verified. The test activities include reduction and analysis of the test data, as appropriate. The following paragraphs define different categories of tests including performance, functional, environmental, interface, and structural tests.

#### **4.1.4.1 Performance Test**

A performance test consists of an individual test or series of electrical and/or mechanical tests conducted on flight, or flight-configured hardware and software at conditions equal to, or less than design specifications. Its purpose is to verify compliance of the test article with the stated applicable specification requirements that are verifiable by test. Typically, a full performance test is conducted at ambient conditions at the beginning and the end of a test sequence during which the test article is subjected to applicable environmental conditions, e.g., vacuum, high/low temperature extremes, or acoustics/random mechanical excitation.

#### **4.1.4.2 Functional Tests**

A functional test is a suitably chosen subset of a performance test. Typically, functional tests are conducted at ambient conditions between environmental exposures during the qualification or acceptance test sequence. The objective is to verify that prior to application of the next environment, exposure to the environment has not adversely affected the test article. When appropriate, functional tests, or a portion thereof, are conducted while the test article is exposed to a particular thermal or vacuum environment. Functional test, or a portion thereof, may also be conducted to assess the state of health of the hardware after major operations, such as transportation of flight hardware from one location to another.

#### **4.1.4.3 Environmental Tests**

Environmental testing is an individual test or series of tests conducted on flight, or flight-configured hardware to assure that flight hardware will perform satisfactorily after it is subjected to the induced launch environments, as well as its flight environment. Examples are: vibration, acoustic, temperature cycling, thermal vacuum and vacuum outgassing certification, and Electromagnetic Interference/Compatibility. Depending on the severity of the chosen environmental conditions, the purpose of the environmental exposure is to sufficiently stress the hardware so as to verify the adequacy of the design (protoflight levels and durations) or workmanship during fabrication (acceptance levels and durations).

#### **4.1.4.4 Special Tests**

Special tests are individual tests, or a series of tests conducted on flight, or flight-configured hardware to assure satisfactory performance of a particular critical element of the system, e.g., optical alignment. The special test verification category includes structural, mechanism and communication tests. Special tests may, or may not be performed in conjunction with environmental exposure.

#### **4.1.4.5 Interface Tests**

Interface tests verify the mechanical, electrical, and/or hardware-software interface between units and elements integrated into a higher level of assembly such as a module, subsystem, element, or a system.

#### **4.1.4.6 Structural Tests**

These tests are performed on structural elements, components, or assembled subsystems before delivery of the assembled structure to the integration and test organization. Structural tests designed to verify requirements of this specification may include: (1) static structural proof tests (to verify the strength/stiffness adequacy of the primary load path), and (2) dynamic tests, such as a modal survey or acoustic response test.

## **4.2 VERIFICATION MATRIX TABLE**

The following matrix table defines the method of verification for all requirements contain in this document:

**Table 4-1. Verification Matrix Table**

Verification Method:

Level:

Inspection (I)

II System

Analysis (A)

III Segment

Demonstration (D)

IV Element

Test (T)

V Subsystem

Requirement Number	Section Number	Object Heading	I	A	D	T	Responsible Org.

**Appendix A. Abbreviations and Acronyms**

<b>Abbreviation/ Acronym</b>	<b>DEFINITION</b>
CCB	Configuration Control Board
CCR	Configuration Change Request
CG	Center of Gravity
CLA	Coupled Loads Analysis
CM	Configuration Management
CMO	Configuration Management Office
dB	decibel
DOF	Degree of Freedom
ELV	Expendable Launch Vehicle
FEM	Finite Element Model
FS	Factors of Safety
g	Acceleration due to Gravity at Earth's Surface (e.g. 9.81 m/s <sup>2</sup> )
GEVS	General Environmental Verification Specification
GN&C	Guidance Navigation and Control
Grms	Root-mean-square Response in g's
GSE	Ground Support Equipment
GSFC	Goddard Space Flight Center
Hz	Hertz
ID	Identification
km	kilometer
KSC	Kennedy Space Center
lbs	pounds
LRO	Lunar Reconnaissance Orbiter
μPa	Micropascal
MECO	Main Engine Cutoff
MGSE	Mechanical Ground Support Equipment
MS	Margin of Safety
MSC	MacNeal Schwendler Corporation
N/A	Not applicable
NASA	National Aeronautics and Space Administration
NASTRAN	NASA Structural Analysis
NSI	Northrop Services Incorporated (now ManTech)
PAF	Payload Adapter Fitting
RP	Reference Publication
RQMT	Requirement
SC	Spacecraft
SPC	Single Point Constraint

A-1

CHECK WITH RLEP DATABASE AT:  
<https://lunarngin.gsfc.nasa.gov>  
 TO VERIFY THAT THIS IS THE CORRECT VERSION PRIOR TO USE.

**Appendix B. Traceability Matrix**

Parent Requirement			Requirement			Child Requirement		
RQMT#	Section#	Object Heading	RQMT#	Section#	Object Heading	RQMT#	Section#	Object Heading

NOTE: Each Requirement must have its own Object Heading.