

Dear Customer,

It is my pleasure to provide you with an updated version of our *Rockot* User's Guide containing revised and updated information on the *Rockot* launch vehicle. The revision is dated April 2001.

Rockot is an established and flight-proven launch vehicle programme which benefits from the strong, market-oriented parentage Astrium and Khrunichev State Research and Production Space Center provide both industrially and financially. The *Rockot* programme also enjoys the guarantees of the Russian and German governments.

Technically, it is a low risk programme supported by a minimum availability of 45 SS-19 booster stages to which the unique, re-ignitable *Breeze-KM* upper stages with a newly enlarged payload envelope are added to form the *Rockot* configuration. The SS-19 has flown 144 times without any failure in the past 16 years and the *Rockot* vehicle a total of 4 times without failure. Since issue (2/1) of the User's Guide the programme has achieved significant milestones. The successful performance of the *Rockot* Commercial Demonstration Flight (CDF) in May 2000 allowed both the new EUROCKOT dedicated processing facilities and pad as well as the larger commercial payload fairing configuration vehicle to be verified. They are now operational for commercial launch services. This new issue (3/1) of the User's Guide reflects the knowledge gained during the CDF.

EUROCKOT has meanwhile firmly established itself as an integral part of the launch provider industry with a number of contracts.

Our User's Guide will acquaint you in detail with the capabilities of both the *Rockot* launch vehicle and the programme management functions EUROCKOT offer as the sole interface and contract partner to the Customer. The User's Guide was designed to serve all customers as an initial reference for all phases of our launch service.

We are dedicated to providing a quick response to any question or request you may have. I therefore invite you to address EUROCKOT members or me personally if we can be of service to you.

Sincerely,

G. Stamerjohanns
CEO
EUROCKOT
Launch Services GmbH

Preface
for Issue 3/1 of ROCKOT User's Guide

This revision of the document is intended to update the completely new issue 3/1 of the *Rockot* User's Guide released in April 2001. This issue includes updates primarily to take into account the extensive experience gained during EUROCKOT's Commercial Demonstration Flight (CDF) performed in May 2000. This flight was performed without anomaly; it was thoroughly instrumented was extremely successful in injecting the spacecraft simulators within 600 metres of their intended orbit; all launch environments measured have confirmed the User's Guide data and in many cases the loads have been revised downwards. The launch site and operations chapters have been thoroughly updated to take into account the newly available state-of-the-art payload and launcher processing facilities.

Essentially, the changes introduced in this new revision can be classified as benign, i.e. generally load magnitudes have been confirmed or reduced and the level of detail in the Guide is much deeper. Hence spacecraft designs compatible to the previous issue will be compatible to this issue.

Bremen, April 2001

EHB-0003, Issue 3, Rev. 1
© 2001 EUROCKOT Launch Services GmbH

Answer Sheet

Please complete and return this form to EUROCKOT by fax to confirm receipt and to obtain documentation upgrade

To:

EUROCKOT Launch Services GmbH

Airport Center Bremen

Flughafenallee 26

D-28199 BREMEN

Germany

Fax: + 49 421 539 - 6500

From:

Name:

Company:

Status or title:

Address:

I have received the ROCKOT User's Guide

Large Version (A4)

Compact Version (A5)

I wish to be considered for corresponding update

Yes

No

I have the following recommendations: _____

I have the following questions: _____

_____ Date

_____ Signature

Rockot User's Guide
Document Change Record

Issue Number	Date	Revised Sheets	Approved
Initial release	30.11.1994	-	Muss
Issue 1	20.01.1995	-	Muss
Issue 1/Rev 1	20.03.1995	1-1, 1-2 2-2, 2-3, Fig. 2-4 deleted 3-1, 3-2, 3-4, 3-6, 3-7, 3-8 4-6, 4-7, 4-17 5-1, 5-2, 5-3, 5-4, 5-7, 5-9 6-3 7-1, 7-2, 7-3, 7-4 8-1, 8-2, 8-3, 8-4, 8-5, 8-6, 8-8, 8-9, 8-10, 8-12, 8-13, 8-14, 8-15, 8-17, 9-1 10-1	Muss
Issue 1/Rev 2	05.07.1995	1-2, 4-6, 4-7	Bamberg
Issue 1/Rev 3	01.08.1995	Fig. 3.1 revised 3.1.2, Fig. 3.2 – 3.4 inserted 4.1.6, Fig. 4.5 revised	Bamberg
Issue 2/Rev 0	11.05.1998	Completely revised issue	Dr. M. Kinnersley Dr. T. Miski
Issue 2/Rev 1	01.06.1999	1-1, Fig. 1-4, 1-5, 1-6 changed, 2-2, Fig. 2-2, 2-3 updated, 2-6, 2-7, 2-8, 2-9, Fig. 3-1 updated, 3-10, 3-11, Fig. 4-3 updated, 4-3, 4-4, Fig. 4-4 updated, 4-8,	

Rockot User's Guide
Document Change Record

Issue Number	Date	Revised Sheets	Approved
continued Issue 2/Rev 1	01.06.1999	Table 5.1.2-1 updated, Table 5.1.3-1 updated, 5-3, Fig. 5-3 updated, Fig. 5-6 updated, Table 5.1.7-1 updated, Table 5.4.1-1 updated, 6-1, Fig. 6-1, 6-2 updated 10-1, 10-6, Fig. 10-3 updated, 10-7, 10-8, Fig. 10-4 updated, 10-12, Fig. 10-5 updated, 10-14, 10-15	Dr. M. Kinnersley Dr. T. Miski
Issue 3/ Rev 0	31.1.01	Completely revised issue taking into account results of CDF and completion of payload processing facilities. In addition performance figures for Baikonur are included now.	Dr. M. Kinnersley Dr. T. Miski
Issue 3/Rev. 1	30.04.01	Editorial changes	Dr. M. Kinnersley Dr. T. Miski

Table of Contents

1	Introduction	1-1
1.1	Reasons for Selecting EUROCKOT	1-4
1.2	EUROCKOT Photograph Gallery	1-4
2	Launch Vehicle Description	2-1
2.1	General Characteristics and Description	2-1
2.1.1	First Stage	2-4
2.1.2	Second Stage	2-5
2.1.3	Upper Composite	2-5
2.1.3.1	Breeze Third Stage	2-5
2.1.3.2	Fairing	2-8
2.1.4	Transport/Launch Container	2-8
2.2	Rockot Qualification, Flight History and Heritage	2-9
2.2.1	Breeze-K Qualification Tests	2-9
2.2.2	Breeze-KM Qualification Tests	2-9
2.2.3	Rockot System Flight Qualification	2-10
2.3	Revalidation of SS-19s used by EUROCKOT	2-11
3	General Performance Capabilities	3-1
3.1	Introduction	3-1
3.2	Launch Azimuths and Orbit Inclinations from Plesetsk	3-1
3.3	Low Earth Orbits	3-2
3.3.1	Payload Performance for Circular Orbits	3-2
3.3.2	Payload Performance for Elliptical Orbits	3-3
3.3.3	Sun-synchronous Orbits (SSO)	3-3
3.4	Mission Profile Description	3-3
3.5	Baikonur Performance	3-13
3.6	Spacecraft Injection and Separation	3-15
3.6.1	Injection Accuracy	3-15

3.6.2	Separation	3-15
3.6.2.1	Spin Stabilised	3-15
3.6.2.2	Three-Axis Stabilised	3-16
3.6.2.3	Typical Multiple Satellite Deployment Scenarios	3-17
4	Spacecraft Interfaces	4-1
4.1	Mechanical Interfaces	4-1
4.1.1	Payload Accommodation	4-1
4.1.2	Usable Volume for Payload	4-2
4.1.3	Spacecraft Accessibility	4-4
4.1.4	Breeze Attachment Point Pattern	4-4
4.2	Payload Adapter and Corresponding Separation System	4-5
4.2.1	Separation Systems	4-5
4.2.1.1	Mechanical Lock Systems	4-5
4.2.1.2	Clamp Band Separation Systems	4-6
4.2.2	Clamp Band Separation System Adapters	4-9
4.2.3	Mechanical Lock System Payload Adapters	4-12
4.2.3.1	Single Satellite Adapters	4-12
4.2.3.2	Multiple Satellite Dispenser Systems	4-13
4.2.3.2.1	Base-mounted Multiple Satellite Dispensers	4-13
4.2.3.2.2	Side-mounted Multiple Satellite Dispensers	4-13
4.3	Electrical Interfaces	4-14
4.3.1	On-board Interfaces	4-14
4.3.1.1	Umbilical Connectors	4-14
4.3.1.2	Separation Verification	4-14
4.3.1.3	Interface Electrical Constraints	4-14
4.3.1.4	Umbilical Harness Configuration and Specifications	4-15
4.3.1.5	Matchmate Electrical Test	4-17
4.3.1.6	Spacecraft Electrical Interface Input Data Requirements	4-18

4.3.2	Ground Electrical Interface	4-18
4.3.2.1	Ground Wiring at Processing Facility	4-18
4.3.2.2	Ground Harness at Launch Site	4-18
4.3.2.3	Ground Wiring Requirements	4-18
4.3.3	Payload Grounding and Bonding	4-20
4.3.4	Payload Auxiliary Power Supply	4-23
4.3.4.1	Ground Auxiliary Power Supply	4-23
4.3.4.2	In-flight Power Supply	4-23
4.3.4.3	Optional Services	4-23
4.3.5	Separation Ignition Command	4-23
4.3.6	Payload Telemetry Support	4-23
5	Spacecraft Environmental Conditions	5-1
5.1	Mechanical Environment	5-1
5.1.1	General	5-1
5.1.2	Quasistatic Accelerations	5-3
5.1.3	Low Frequency Vibration	5-3
5.1.4	Acoustic Noise	5-3
5.1.5	Random Vibration	5-6
5.1.6	Shock	5-6
5.1.7	Loads during Transportation and Handling	5-7
5.2	Thermal Environment	5-13
5.2.1	General	5-13
5.2.2	Environmental Conditions in the Preparation Building	5-13
5.2.3	Pre-Launch Temperature Control within the Fairing	5-13
5.2.4	In-Flight Temperature under the Fairing	5-17
5.2.5	Aerothermal Flux at Fairing Jettisoning	5-17
5.2.6	Heat Impact during the Coasting Phase	5-17
5.3	Fairing Static Pressure during the Ascent	5-18
5.4	Contamination and Cleanliness	5-18
5.5	Electromagnetic Environment	5-18
5.5.1	Launch Vehicle	5-19

5.5.2	EMC Requirements for the Spacecraft	5-19
6	Spacecraft Design and Verification Requirements	6-1
6.1	Safety Requirements	6-1
6.2	Selection of Payload Materials	6-1
6.3	Design Characteristics	6-1
6.3.1	Center of Gravity Constraints	6-1
6.3.2	Spacecraft Balancing	6-1
6.3.2.1	Static Imbalance	6-1
6.3.2.2	Dynamic Imbalance	6-3
6.3.3	Structural Integrity	6-3
6.3.3.1	Factors of Safety	6-3
6.3.3.2	Dimensioning Loads	6-3
6.3.4	Stiffness	6-4
6.3.5	Overflux	6-4
6.4	Spacecraft Compatibility Tests	6-4
6.4.1	Spacecraft Mechanical Qualification and Acceptance Tests	6-4
6.4.1.1	Static Load Test	6-5
6.4.1.2	Sinusoidal Vibration Test	6-5
6.4.1.3	Random Vibration Test	6-5
6.4.1.4	Acoustic Noise Test	6-6
6.4.1.5	Shock Test	6-6
6.4.2	Interface Tests	6-6
7	Mission Management	7-1
7.1	Mission Management Overview	7-1
7.2	Organisation and Responsibilities	7-1
7.2.1	EUROCKOT Mission Responsibilities	7-3
7.2.1.1	Mission Integration/ Mission Analysis	7-3

	7.2.1.2	Interface Verification	7-4
	7.2.1.3	Configuration Control	7-5
	7.2.1.4	Launch Vehicle Procurement	7-5
	7.2.1.5	Spacecraft Preparation/ Launch Operations	7-5
	7.2.1.6	Post-Launch Activities	7-5
	7.2.1.7	Quality Assurance/ Mission Assurance	7-6
	7.2.1.8	Safety Provisions	7-6
	7.2.1.9	Risk Management	7-6
	7.2.1.10	Technology Transfer/ Security	7-7
	7.2.2	Customer Mission Responsibilities	7-7
7.3		Reviews and Documentation	7-8
	7.3.1	EUROCKOT Documents	7-9
	7.3.2	Customer Documents	7-11
7.4		Overall Mission Schedule	7-11
8		Mission Analysis	8-1
	8.1	General	8-1
	8.2	Trajectory and Mission Sequence	8-1
	8.3	Dynamics of Spacecraft Separation	8-2
	8.4	Dynamic Coupled Loads Analysis	8-3
		8.4.1 Coupled Loads Analysis Scope	8-4
		8.4.2 Coupled Loads Analysis Report	8-4
		8.4.3 Requirements for Spacecraft Mathematical Model	8-4
	8.5	Eelctromagnetic Compatibility Study	8-5
	8.6	Thermal Environment	8-6
	8.7	Cleanliness Analysis	8-6
9		Safety	9-1
	9.1	Introduction	9-1
	9.2	Submission Procedure	9-1
		9.2.1 Phase I Safety Submission	9-1

9.2.2	Phase II Safety Submission	9-3
9.2.3	Phase III Safety Submission	9-3
9.3	Safety Submission Contents and Requirements	9-3
9.3.1	Release of Safety Statements	9-3
9.3.2	Final Date for Submission	9-3
9.3.3	Applicability	9-4
9.3.4	Identification of Statements	9-4
9.4	Spacecraft Safety Data Package Contents	9-4
9.4.1	Hazardous Systems	9-4
9.4.2	Guidelines for Safety Analyses	9-4
9.4.2.1	Overall Assessment of Risk and Severity	9-4
9.4.2.2	Threat of Danger	9-5
9.4.2.3	Prevention of Danger	9-5
9.4.2.4	Reference Documents	9-5
9.5	Non-compliance with Safety Requirements/ Waivers	9-6
9.6	Summary	9-6
10	Plesetsk Cosmodrome	10-1
10.1	General Description	10-1
10.1.1	Climatic Conditions	10-3
10.2	Logistics	10-3
10.2.1	Hardware Transport	10-3
10.2.1.1	Transport Flow by Air	10-4
10.2.1.2	Transport Flow by Rail	10-5
10.2.2	Transport Requirements	10-5
10.2.3	Transport Environments	10-5
10.2.3.1	Environmentally Controlled Transport of Spacecraft during the Launch Campaign	10-5
10.2.4	Spacecraft Team Transport to Plesetsk Cosmodrome	10-6
10.2.4.1	Charter Aircraft	10-6
10.2.4.2	Scheduled Flights	10-6
10.2.4.3	Rail Transfer to Plesetsk Cosmodrome	10-7

10.2.4.4	Transfer by Car or Bus from Archangel to Plesetsk Cosmodrome	10-7
10.2.5	Customer Team Transport at the Launch Site	10-7
10.3	Communications	10-7
10.3.1	Phone Lines	10-7
10.3.2	Data Lines	10-8
10.3.3	Mobile Radios	10-8
10.3.4	CCTV	10-8
10.3.5	Entertainment TV	10-9
10.4	Ground Facilities	10-9
10.4.1	Areas Intended for Sole Customer Use	10-9
10.4.2	The Integration Facility MIK	10-9
10.4.2.1	General Hall	10-12
10.4.2.2	Clean Room Bay	10-12
10.4.2.2.1	Airlock	10-12
10.4.2.2.2	Upper Composite Integration Area	10-12
10.4.2.2.3	Spacecraft Processing Area	10-13
10.4.2.3	EGSE Rooms	10-14
10.4.2.4	Customer's Office Area	10-15
10.4.2.5	Handling and Hoisting Equipment in MIK	10-15
10.4.2.6	Power Supply of MIK	10-15
10.4.3	The Rockot Launch Complex	10-18
10.4.3.1	Launch Pad	10-19
10.4.3.2	Blockhouse	10-21
10.4.3.3	Power Supply of Launch Complex	10-22
10.4.3.4	Air Conditioning of the Spacecraft and Spacecraft Batteries at the Launch Pad	10-23
10.4.4	The Mission Control Centre	10-23
10.5	Launch Campaign	10-24
10.5.1	Responsibilities and Operational Organisation	10-24
10.5.2	Planning	10-25

10.5.3	Procedures and Logbook of Works	10-25
10.5.4	Training / Briefings	10-25
10.5.5	Security Access and Control	10-26
10.5.6	Safety	10-26
10.5.7	Launch Campaign Operations	10-26
10.5.7.1	Launch Vehicle Operations in the MIK	10-27
10.5.7.2	Spacecraft Operations	10-29
10.5.7.3	Combined Operations	10-30
10.5.7.4	Launch Operations at the Launch Pad	10-31
10.5.8	Launch Day Decision Flow	10-33
10.5.9	Abort Re-cycle / Return-to-Base Operation	10-34
10.6	Accommodation and Leisure Activities	10-34
10.7	Medical Care	10-35
11	Baikonur Cosmodrome	11-1
12	Items to be Delivered by the Customer	12-1
12.1	General Documents	12-2
12.2	Data on Payload Design	12-3
12.3	Payload Environmental Test Documents	12-5
12.4	Operations Documents for Spacecraft	12-6
12.5	Models, GSE	12-7
12.6	Hardware, Software and Document Time Schedule	12-8

List of Figures

Figure 1-1:	Shareholders in the EUROCKOT Joint Venture	1-2
Figure 1-2:	EUROCKOT Roles and Responsibilities	1-3
Figure 1-3:	Close-up of Rockot CDF Launch from Plesetsk	1-5
Figure 1-4:	Long Distance View of CDF Launch from EUROCKOT's Payload Processing Facilities	1-6
Figure 1-5:	Integration of SIMSAT Payload with Breeze in EUROCKOT's Payload Processing Facility	1-7
Figure 1-6:	Beginning of Payload Encapsulation	1-8
Figure 1-7:	Close-up of Payload Fairing in EUROCKOT's Payload Processing Facility	1-9
Figure 1-8:	Completion of Encapsulation	1-9
Figure 1-9:	Transport of the Upper Composite Including Payload from Clean Room to Main Hall	1-10
Figure 1-10:	Fitting of Thermal Cover on Upper Composite Prior to Transfer to the Launch Pad	1-11
Figure 1-11:	Upper Composite Installed on Rail Car Connected to Mobile Air Conditioning Unit	1-12
Figure 1-12:	Booster Installation at the Pad	1-12
Figure 1-13:	Beginning of Operations for Mating the Upper Composite with the Rockot Booster Stage (SS-19)	1-13
Figure 1-14:	Stacking of Upper Composite on the Rockot Booster (SS-19)	1-14
Figure 1-15:	Rockot Launch Vehicle Ready for Launch with Mobile Service Tower Rolled Back	1-15
Figure 1-16:	The Rockot Launch Vehicle Booster (SS-19) contained within its Transport and Launch Container in the Khrunichev Facilities, Moscow	1-16
Figure 1-17:	Close-up of the Breeze Restartable Upper Stage in the Khrunichev Production Hall	1-16

Figure 1-18:	Aft View of the Breeze Stage Propulsion Compartment	1-17
Figure 1-19:	Breeze Production Hall	1-17
Figure 1-20:	Mobile Air Conditioning Unit	1-18
Figure 1-21:	Transport Unit T3Y-68P for Transport of Breeze Stage to and from Fuelling Facility	1-18
Figure 1-22:	YAK-40 Aircraft for Personnel Transportation to and from the Plesetsk Launch Site	1-19
Figure 1-23:	EUROCKOT Integration Facility "MIK" with Main Hardware Entrance Door Depicted	1-19
Figure 1-24:	EUROCKOT Clean Room Bay	1-20
Figure 1-25:	Removable Fuelling Platform for Hydrazine Spacecraft Installed within the Spacecraft Processing Area	1-20
Figure 1-26:	Mobile Service Tower and Stationary Column	1-21
Figure 1-27a:	Hotel Rocket	1-22
Figure 1-27b:	Hotel Rocket	1-22
Figure 1-28:	Typical Vibration Tests of a Breeze Upper Stage with Spacecraft Mass-Frequency Simulators (GRACE)	1-23
Figure 1-29:	Typical Test of Separation of Spacecraft Simulators from the Breeze Upper Stage (GRACE)	1-24
Figure 2-1:	Launch Vehicle's Major Axes	2-2
Figure 2-2:	Rocket Launch Vehicle Configuration	2-3
Figure 2-3:	Upper Composite with Payload	2-6
Figure 3-1 (1):	Breeze-KM Sun orientation during drift phase	3-4
Figure 3-1 (2):	Breeze-KM Sun orientation during drift phase	3-4
Figure 3-2:	Performance Capabilities for Circular Orbits	3-6
Figure 3-3:	Performance for Elliptical Orbits at $i = 63^\circ$	3-7
Figure 3-4:	Performance for Elliptical Orbits at $i = 75.3^\circ$	3-8
Figure 3-5:	Performance for Elliptical Orbits at $i = 82^\circ$	3-9
Figure 3-6:	Ascent trajectory for LEO 300 km	3-10
Figure 3-7:	Ascent sequence for LEO 300 km	3-10
Figure 3-8:	Ascent trajectory for LEO 700 km	3-11
Figure 3-9:	Flight sequence for LEO 700 km	3-11

Figure 3-10:	Ascent Trajectory for a 800 km/98.6 deg inclined SSO	3-12
Figure 3-11:	Flight Sequence for a 800 km/96.8 deg inclined SSO	3-12
Figure 3-12:	Sun-synchronous Injection Scheme	3-13
Figure 3-13:	Payload Performance for Circular Orbits from Baikonur Cosmodrome	3-14
Figure 3-14:	Performance for Elliptical Orbits from Baikonur Cosmodrome	3-14
Figure 3-15:	Multiple Payload Deployment Scheme	3-18
Figure 3-16:	Simultaneous Deployment of Six Spacecraft	3-18
Figure 4-1:	Multiple Payload Accommodation (one level)	4-1
Figure 4-2:	Multiple Payload Accommodation (two levels)	4-2
Figure 4-3:	Rockot Maximum Usable Payload Envelope	4-3
Figure 4-4:	Breeze Attachment Point Pattern	4-4
Figure 4-5:	Cut-away Detail of the Mechanical Lock System	4-6
Figure 4-6:	SAAB 937 Clamp Band Adapter	4-7
Figure 4-7:	CASA 1194 Clamp Ring Adapter with 30 kN Pre-Load	4-8
Figure 4-8a:	Clamp Band Cylindrical Payload Adapter with 937 mm Interface Ring	4-9
Figure 4.8b:	Interface Ring Detail of the 937 mm Clamp Band Cylindrical Payload Adapter	4-10
Figure 4-9a:	1194 mm Clamp Band Conical Payload Adapter	4-10
Figure 4-9b:	Interface Ring Detail of the 1194 mm Clamp Band Conical Payload Adapter	4-11
Figure 4-9c:	Interface Ring Detail of the 1194 mm Clamp Band Conical Payload Adapter	4-11
Figure 4-10:	Adapter System for Single Satellite Accommodation using the Mechanical Lock System	4-12
Figure 4-11:	Payload Arrangement Option on Breeze-KM Interface Plane	4-13
Figure 4-12:	Side-mounted Multiple Satellite Dispenser for Two Spacecraft	4-14
Figure 4-13:	Typical Example of an Umbilical Connector Bracket for 1194 mm Clamp Band	4-15

Figure 4-14:	Umbilical Connector OSRS50B	4-16
Figure 4-15:	Rockot Umbilical Harness Diagram	4-19
Figure 4-16:	Launch Site Ground Wiring Diagram	4-20
Figure 4-17:	Bonding/Grounding Schematic Drawing Example of a Dispenser Configuration	4-22
Figure 5-1:	Launch Vehicle and Payload Coordinate System	5-1
Figure 5-2:	Variation of Longitudinal Static Accelerations during Flight	5-2
Figure 5-3:	Low Frequency Vibration Environment at Separation Plane	5-4
Figure 5-4:	Acoustic Noise under the Fairing	5-4
Figure 5-5:	Shock Environment	5-7
Figure 5-6:	Transportation of Spacecraft in Transportation Container	5-8
Figure 5-7:	Spacecraft Transportation as Part of the Upper Composite	5-8
Figure 5-8:	Random Vibration Spectra at Adapter / Breeze Interface during Transportation of the SH	5-10
Figure 5-9:	Acceleration Spectral Density for Helicopter	5-11
Figure 5-10:	Acceleration Spectral Density for Road	5-11
Figure 5-11:	Acceleration Spectral Density for Transportation in Upper Composite	5-13
Figure 5-12:	Air Conditioning of the Upper Composite at the Launch Pad	5-16
Figure 5-13:	Air Conditioning of Upper Composite during Transportation	5-17
Figure 5-14:	Variation of Fairing Static Pressure during the Ascent	5-18
Figure 5-15:	Launch Vehicle RF Environment	5-20
Figure 5-16:	Restrictions on RF Use by the Spacecraft during Launch	5-20
Figure 6-1:	Spacecraft CoG Constraints	6-2
Figure 6-2:	Definition of Upper Composite CoG	6-2
Figure 6-3:	Typical Limit Load Factors for Initial Dimensioning of Secondary Structures and Equipment Brackets	6-3
Figure 7-1:	Industrial Organisation of EUROCKOT and its Subcontractors	7-2
Figure 7-2:	EUROCKOT Mission Management Organisation	7-3
Figure 7-3:	Typical Mission Schedule	7-12
Figure 8-1:	Mission Analysis Overview	8-1

Figure 9-1:	Safety Submission Phases	9-2
Figure 10-1:	Geographical Location of Plesetsk Cosmodrome	10-1
Figure 10-2:	Plesetsk Cosmodrome Layout	10-2
Figure 10-3:	Layout of Integration Facility ,MIK'	10-11
Figure 10-4:	Layout of Removable Fuelling Platform	10-14
Figure 10-5:	Customer Office Area in MIK	10-16
Figure 10-6:	The Launch Complex for Rockot	10-18
Figure 10-7:	Launch Pad	10-20
Figure 10-8:	Undertable Rooms for Customer's Use	10-21
Figure 10-9:	Customer Rooms in the Blockhouse with Location of Phones and LAN Drops	10-22
Figure 10-10:	Schedule of Operations	10-27
Figure 10-11:	Scheme of Combined Operations	10-30
Figure 10-12:	Pad Operations	10-32
Figure 12-1:	IRD Table of Contents	12-2
Figure 12-2:	Spacecraft Operations Plan (SOP) - Table of Contents	12-6
Figure 12-3:	Schedule for Documents, Software and Hardware to be Supplied by the Customer	12-9

Abbreviations

AC	Alternating Current
AOCS	Attitude and Orbit Control System
CCTV	Closed-circuit Television
CDF	Commercial Demonstration Flight
CDR	Critical Design Review
CEO	Chief Executive Officer
CIS	Commonwealth of Independent States
CLA	Coupled Loads Analysis
CoG	Centre of Gravity
COP	Combined Operations Plan
DC	Direct Current
DPA	Destructive Physical Analysis
DT	Direct Transmission Mode (Telemetry)
DTSA	Defense Technology Security Agency
EGSE	Electrical Ground Support Equipment
EMC	Electromagnetic Compatibility
FMAD	Final Mission Analysis Documentation
FMAR	Final Mission Analysis Review
FS	Factor of Safety
GMF	Ground Measurement Facility
GMI	Ground Measurement Infrastructure
GN2	Gaseous Nitrogen
GPS	Global Positioning System (US),
GLONASS	Global Navigation Space System (CIS)
GSE	Ground Support Equipment
ICBM	Intercontinental Ballistic Missile
ICD	Interface Control Document
IRD	Interface Requirements Document
KSRC	Khrunichev State Research and Production Space Center
LCR	Launch Control Room
LER	Launch Evaluation Report

LOS	Launch Operation Schedule
LRD	Launch Requirements Document
LRR	Launch Readiness Review
LSM	Launch Service Manager
LV	Launch Vehicle
LVM	Launch Vehicle Manager
MA	Mission Assurance
MAR	Mission Analysis
MCC	Mission Control Centre
MGSE	Mechanical Ground Support Equipment
MIK	Spacecraft Integration Facility for ROCKOT in Plesetsk
MLS	Mechanical Lock System
MM	Mission Manager
Mol	Moment of Inertia
N2O4	Nitrogen Tetroxide (Oxidizer)
O(A)SPL	Overall Sound Pressure Level
PDR	Preliminary Design Review
PLF	Payload Fairing
PMAD	Preliminary Mission Analysis Documentation
PMAR	Preliminary Mission Analysis Review
PSD	Power Spectral Density
QA	Quality Assurance
REC	Data Record Mode (Telemetry)
REP	Data Replay Mode (Telemetry)
RF	Radio Frequency
RMS	Root Mean Square
RPM	Revolutions per Minute
S/C	Spacecraft
SDR	Systems Design Review
SMD	Spacecraft Mission Director
SOP	Spacecraft Operations Plan
SOTP	Spacecraft Operations Test Procedure
SPPA	Single Pyro Released Point Attachment System
SSO	Solar Synchronous Orbit

TA1	ROCKOT Low Rate Telemetry Device
TA2	ROCKOT High Rate Telemetry Device
TAA	Technical Assistance Agreement
TIM	Technical Interchange Meeting
TLC	Transport and Launch Container
UDMH	Unsymmetrical Dimethyl Hydrazine (Fuel)